




POWER & EFFICIENCY

INPUT POWER OPTIONS	AC 1PH 200-240V 50/60Hz AC 3PH 200-240V 50/60Hz AC 3PH 380-480V 50/60Hz		
MAXIMUM RATED CURRENT (amp)	7.0 A		3.5 A 2.0 A
POWER (hp)	5/8 HP		
MAXIMUM SPEED (RPM)	100 RPM		
CFM	120,000		

DIMENSIONS & WEIGHT

FAN DIAMETER	14 ft
FAN WEIGHT	128 lbs (58 kg)



The technical drawing shows a side profile of the Hunter ECO 14 fan. It is a long, thin, horizontal unit. A central vertical support structure is shown. Dimension lines indicate a total length of 14 ft. A vertical dimension line on the left is labeled '(A) MINIMUM 2 ft'. A horizontal dimension line on the right is labeled '5 INCH (127MM)'. The drawing is labeled 'Pictured with 2 ft downrod'.

MOUNTING & SAFETY

MOUNTING OPTIONS	I-beam Glulam
DOWNROD (A)	Downrods available in 1 ft increments: 2 ft min., 10 ft max. Downrod length must be specified at time of order.
SAFETY FEATURES	Fan Retention System Airfoil Retention System Fire relay

IN THE BOX

INCLUDED	Fan I-beam mount with pre-wired downrod Control panel Install manual Wall Control Mounting hardware kit Communication Kit Guy wire kit
OPTIONAL	Additional cable lengths Network Controller Glulam brackets

WARRANTY & CERTIFICATIONS

CERTIFICATIONS	ETL/Intertek-certified to ANSI/UL 507 and CSA C22.2 No. 113 in North America
WARRANTY ¹	10-year, Non-Prorated Warranty

¹See complete warranty for details.