




POWER & EFFICIENCY

INPUT POWER OPTIONS	AC 1PH 200-240V 50/60Hz   AC 3PH 200-240V 50/60Hz   AC 3PH 380-480V 50/60Hz		
MAXIMUM RATED CURRENT (amp)	7.0 A		3.5 A   2.0 A
POWER (hp)	5/8 HP		
MAXIMUM SPEED (RPM)	70 RPM		
CFM	215,000		

DIMENSIONS & WEIGHT

FAN DIAMETER	20 ft
FAN WEIGHT	145 lbs (66 kg)



The technical drawing shows a side profile of the Hunter ECO 20 fan. It is a long, thin, horizontal unit. A central vertical support structure is shown. Dimension lines indicate a total length of 20 ft. A vertical dimension line on the left is labeled '(A) MINIMUM 2 ft'. A horizontal dimension line on the right is labeled '5 INCH (127MM)'. The drawing is labeled 'Pictured with 2 ft downrod'.

MOUNTING & SAFETY

MOUNTING OPTIONS	I-beam   Glulam
DOWNROD (A)	Downrods available in 1 ft increments: 2 ft min., 10 ft max. Downrod length must be specified at time of order.
SAFETY FEATURES	Fan Retention System   Airfoil Retention System   Fire relay

IN THE BOX

INCLUDED	Fan I-beam mount with pre-wired downrod   Control panel   Install manual Wall Control   Mounting hardware kit   Communication Kit   Guy wire kit
OPTIONAL	Additional cable lengths   Network Controller   Glulam brackets

WARRANTY & CERTIFICATIONS

CERTIFICATIONS	ETL/Intertek-certified to ANSI/UL 507 and CSA C22.2 No. 113 in North America
WARRANTY <sup>1</sup>	10-year, Non-Prorated Warranty

<sup>1</sup>See complete warranty for details.